

# DIELECTRIC RESONATOR OSCILLATOR



## SURFACE MOUNT MODEL: SDRO740-8

### FREQUENCY

### 7.4 GHz


#### FEATURES:

- ▶ Extended Operating Temperature Range
- ▶ Exceptional Phase Noise Performance
- ▶ Small Size Surface Mount
- ▶ Lead Free RoHS Compliant



#### SPECIFICATIONS

Frequency	7.4 GHz	
Tuning Voltage	1 - 10 VDC	
Bias Voltage	+8 VDC @ 30 mA (Max.)	
Output Power	5 dBm (Min.)	
Tuning Sensitivity	1 MHz/V (Typ.)	
Thermal Drift	2.3 ppm / °C (Typ.)	
Output Impedance	50 Ohms (Nom.)	
Harmonic Suppression	15 dBc (Typ.)	
Frequency Pulling	1 MHz (Typ. @ 1.75:1 VSWR)	
Frequency Pushing	50 MHz/V (Typ.)	
Tuning Port Capacitance	10 pF (Typ.)	
Phase Noise @ 25°C	Offset	dBc/Hz (Typ.)
	10 kHz	-111
	100 kHz	-138
	1 MHz	-160
Operating Temperature Range	-15 to +75 °C	



#### Absolute Maximum Ratings

Storage Temp. Range	-40 to +85 °C
Bias Voltage	+8.5 V
Tuning Voltage	+16 V
DC Voltage Applied to RF Out	±25 V

#### Notes:



1. Tuning of the mechanical screw can cause significant shifts in frequency and cause irreversible damage to the product. Warranty is void if tuning screw exceeds ±0.5 turn max.
2. Test data measured with bias voltage at +8V.
3. Specifications guaranteed at 7.4 GHz.

# DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO740-8

FREQUENCY

7.4 GHz

PERFORMANCE PLOTS





# DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO740-8

FREQUENCY

7.4 GHz


PERFORMANCE PLOTS



# DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO740-8

FREQUENCY

7.4 GHz



PERFORMANCE PLOTS