



DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDR0900-8XT

FREQUENCY

9 GHz


FEATURES:

- ▶ Extended Operating Temperature
- ▶ Exceptional Phase Noise Performance
- ▶ Small Size Surface Mount
- ▶ Lead Free RoHS Compliant



SPECIFICATIONS

Frequency	9 GHz	
Tuning Voltage	1 - 10 VDC	
Bias Voltage	+8 VDC @ 25 mA (Max.)	
Output Power	+1 dBm (Min.)	
Tuning Sensitivity	1 MHz/V (Typ.)	
Thermal Drift	5 ppm / °C (Typ.)	
Output Impedance	50 Ohms (Nom.)	
Harmonic Suppression	21 dBc (Typ.)	
Frequency Pulling	1 MHz (Typ. @ 1.75:1 VSWR)	
Frequency Pushing	400 kHz/V (Typ.)	
Tuning Port Capacitance	10 pF (Typ.)	
Phase Noise @ 25 °C	Offset	dBc/Hz (Typ.)
	10 kHz	-112
	100 kHz	-132
	1 MHz	-152
	10 MHz	-165
Operating Temperature Range	-40 to +85 °C	



Absolute Maximum Ratings

Storage Temp. Range	-45 to +90 °C
Bias Voltage	+8.5 V
Tuning Voltage	+16 V
DC Voltage Applied to RF Out	±25 V

Notes:



1. Tuning of the mechanical screw can cause significant shifts in frequency and cause irreversible damage to the product. Warranty is void if tuning screw exceeds ±0.5 turn max.
2. Test data measured with bias voltage at +8V.
3. Specifications guaranteed at 9 GHz.

DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO900-8XT

FREQUENCY

9 GHz

PERFORMANCE PLOTS





DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO900-8XT

FREQUENCY

9 GHz


PERFORMANCE PLOTS



DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO900-8XT

FREQUENCY

9 GHz



PERFORMANCE PLOTS