



VOLTAGE CONTROLLED SAW OSCILLATOR

SURFACE MOUNT MODEL: HFSO2000-5

2000 MHz

FEATURES:


- ▶ Exceptional Phase Noise Performance
- ▶ Small Size, Surface Mount
- ▶ Lead Free REL-PRO® Technology
- ▶ Buffered Output



SPECIFICATIONS (Rev. D 09/01/20)

Frequency	2000 MHz	
Tuning Voltage	0.5 - 12 VDC	
Bias Voltage (Vcc)	+5 VDC ($\pm 5\%$) @ 100 mA (Max.)	
Output Power	+6 dBm (Min.)	
Tuning Sensitivity	35 kHz/V (Typ.)	
Thermal Drift	300 kHz (Typ.)	
Output Impedance	50 Ohms (Nom.)	
Harmonic Suppression		dBc (Typ.)
	2nd	20
3rd	20	
Sub-Harmonic Suppression	20 dBc (typ.)	
Frequency Pulling	15 kHz (Typ. @ 1.75:1 VSWR)	
Frequency Pushing	20 kHz/V (Typ.) Vcc $\pm 5\%$	
Tuning Port Capacitance	55 pF (Typ.)	
Phase Noise @ 25 °C	Offset	dBc/Hz (Typ.)
	@ 10 kHz	-137
@ 100 kHz	-159	
Operating Temperature Range	-20 to +70 °C	

Package # 320-2LF



Absolute Maximum Ratings

Storage Temp. Range	-30 to +85 °C
Bias Voltage	+5.5 V
Tuning Voltage	+15 V
DC Voltage Applied to RF Out	± 25 V

Patent : <http://www.synergymwave.com/patents>

Copyright © Synergy Microwave Corporation
 201 McLean Boulevard • Paterson, New Jersey 07504 USA
 Tel: (973) 881-8800 • Fax: (973) 881-8361
 E-Mail: sales@synergymwave.com • Website: <http://www.synergymwave.com>
 Patents : <http://www.synergymwave.com/patents>





VOLTAGE CONTROLLED SAW OSCILLATOR

SURFACE MOUNT MODEL: HFSO2000-5

2000 MHz



PERFORMANCE PLOTS



VOLTAGE CONTROLLED SAW OSCILLATOR SURFACE MOUNT MODEL: HFSO2000-5

2000 MHz

PERFORMANCE PLOTS



VOLTAGE CONTROLLED SAW OSCILLATOR SURFACE MOUNT MODEL: HFSO2000-5

2000 MHz

PERFORMANCE PLOTS

